FOUR-WAY FLOAT TOP RADIOGRAPHIC TABLE

STYLIX 2

STYLIX 2

Four-way Float Top Radiographic Table

Simplicity, Performance and Safety

The Stylix 2 radiographic table's heavy-duty, compact, space-saving design provides exceptional versatility and allows for installations in small x-ray rooms.

While the four-way float top glides effortlessly on it's precision bearing system and the convenient location of the foot pedal, which controls all tabletop movements, the Stylix 2 radiographic table is the excellent choice when searching for a durable and reliable radiographic table.



www.cxmed.com

STYLIX 2

CONTROL-X MEDICAL

FOUR-WAY FLOAT TOP RADIOGRAPHIC TABE

TABLETOP MOVEMENT

The large, easy-to-clean tabletop's precision bearing system ensures effortless patient positioning. Combined with the extended Bucky travel, the Stylix 2 enables full coverage the entire length of the table.

MOTION CONTROLS

The conveniently located foot pedal initiates all table movements for safe and accurate exposure positioning.

HIGH QUALITY MATERIALS

The low absorption tabletop material reduces exposure dose rate while the small skin-film distance permits precise, low magnification film studies. Standard side rails support a wide variety of accessories.


MODEL DIVERSITY


Accepts standard non size-sensing and size-sensing grid cabinets or reciprocating buckys, matching trays and grids while still leaving enough room for AEC chambers.

DIGITAL COMPATIBILITY

Adding CR or DR is now easier than ever due to the new Bucky carriage design. Specialized mounting hardware for different digital panels is available upon request.

STYLIX 2	SPECIFICATIONS
Tabletop length	86" (220 cm) (Optional 73" (185 cm))
Tabletop width	32" (81 cm)
Film-tabletop distance	3" (7,5 cm)
Longitudinal travel	43" (110 cm)
Transverse travel	± 4.75" (± 12 cm)
Grid cabinent / Bucky travel	22.5″ (57 cm)
Weight limit	500 lbs (226,8 kg)
Cassette sizes	All sizes up to a format of 17" x 17" (43 x 43 cm)
Tabletop absorption density	< 0,80 mm Al equivalent
Power requirements	24 VAC ±10", 50/60 Hz, 1.5 A current consumption
Optional accessories	Head clamp Hip clamp Compression belt Lateral cassette holder





For more information, please visit our website at www.cxmed.com or contact your local authorized distributor.





Control-X Medical 1755 Atlas Street, Columbus, OH 43228, USA Tel: 1-614-777-9729 Toll free: 1-800-777-9729 Fax: 1-614-777-0395 E-mail: sales@cxmed.com Web: www.cxmed.com

www.cxmed.com

© 2012, Control-X Medical. All rights reserved The manufacturer reserves the right to change specifications and features without notice